

# Industrial Speciality Gas Cylinders

## Specifications

Sales Part Number	Service Pressure		Capacity N <sub>2</sub>		Capacity O <sub>2</sub>		Outside Diameter		Overall Length		Empty Weight		Min. Internal Volume		Min. Water Weight		Thread Size UNF
	psi	bar	cu ft	liters	cu ft	liters	in	mm	in	mm	lbs	kg	cu in	liters	lbs	kg	
<b>N004</b>	2216	153	3.7	103.4	4.0	114.1	3.21	81.41	9.0	228.6	1.9	0.8	43	0.7	1.53	0.70	0.750-16 UNF-2B
<b>N006</b>	2216	153	5.3	150.7	5.8	164.5	3.21	81.41	11.8	299.0	2.2	1.0	62	1.0	2.24	1.01	0.750-16 UNF-2B
<b>N007</b>	2015	139	6.8	193.7	7.4	209.6	4.38	111.13	9.2	233.2	3.0	1.4	87	1.4	3.14	1.42	0.750-16 UNF-2B
<b>N009</b>	2015	139	8.1	229.4	8.8	248.4	4.38	111.13	10.6	269.9	3.7	1.7	103	1.7	3.71	1.68	0.750-16 UNF-2B
<b>N011</b>	2015	139	10.9	307.3	11.7	332.5	4.38	111.13	13.8	350.8	4.7	2.1	138	2.3	4.98	2.26	0.750-16 UNF-2B
<b>N022</b>	2216	153	20.9	591.9	22.9	647.1	5.25	133.35	17.1	435.1	8.8	4.0	244	4.0	8.80	3.99	0.750-16 UNF-2B, 0.750-14 NGT, 1.125-12 UNF-2B
<b>N027</b>	2216	153	25.3	716.5	27.6	782.2	5.25	133.35	20.2	513.5	10.4	4.7	295	4.8	10.64	4.83	1.125-12 UNF-2B
<b>N033</b>	2216	153	30.9	875.1	33.7	954.4	6.89	175.01	15.6	396.9	14.5	6.6	360	5.9	12.98	5.89	0.750-16 UNF-2B, 0.750-14 NGT, 1.125-12 UNF-2B
<b>N042</b>	2216	153	44.2	1252.0	48.2	1365.6	5.25	133.35	33.1	841.5	16.0	7.2	515	8.4	18.57	8.42	0.750-14 NGT
<b>N060</b>	2216	153	55.8	1580.0	60.9	1723.6	7.25	184.15	23.5	596.9	22.6	10.2	650	10.7	23.44	10.63	0.750-14 NGT, 1.125-12 UNF-2B, M25 x 2
<b>N088</b>	2216	153	82.4	2333.6	89.9	2545.7	7.25	184.15	32.9	835.0	30.7	13.9	960	15.7	34.62	15.70	0.750-14 NGT, 1.125-12 UNF-2B
<b>N122</b>	2216	153	111.8	3165.0	121.9	3452.5	8.00	203.20	36.3	922.3	40.0	18.1	1302	21.3	46.95	21.30	0.750-14 NGT, 1.125-12 UNF-2B
<b>N150</b>	2015	139	141.5	4007.6	153.2	4338.3	8.00	203.20	47.8	1214.5	48.1	21.8	1800	29.5	64.91	29.44	0.750-14 NGT, 1.125-12 UNF-2B
<b>N155</b>	1800	124	144.3	4086.6	154.8	4383.4	8.60	218.44	46.3	1176.7	50.6	22.9	2040	33.4	73.56	33.37	1.125-12 UNF-2B
<b>N200</b>	3000	207	178.2	5047.2	200.2	5669.9	8.60	218.44	40.7	1034.9	64.6	29.3	1590	26.1	57.32	26.00	0.750-14 NGT, 1.125-12 UNF-2B
<b>N265</b>	2216	153	243.0	6881.8	265.1	7506.8	9.80	248.92	51.9	1319.0	87.0	39.5	2831	46.4	102.08	46.30	0.750-14 NGT, 1.125-12 UNF-2B

3016 Kansas Avenue, Riverside, CA 92507 USA,  
 Tel: (909) 684 5110 or (800) 764 0366 Fax: (909) 781 6598

